

2AMCV718WDPS

Auto-addressable WIFI/DALI converter with integrated BUS DALI power supply

Device Wifi to DALI converter with push interface.

Integrated DALI bus power supply for up to 16 devices.

Input Range: 100-240V AC 50/60Hz.

Controllable with Android/iOS app IoT Light Smart.

Input Controls				
Туре	Qty			
Not insulated Push button	1			
Wifi	1			

Output Sync			
Туре	Qty		
DALI	1		



TECHNICAL NOTES

- Device Wifi to DALI converter with push interface.
- Integrated DALI bus power supply for up to 16 devices.
- Input Range: 100-240V AC 50/60Hz.
- The device is not equipped with earth connection

Protection against accidental contact with live parts is garantied by the enclosure.

- Power Connector Cross-section of conductors 14-30 AWG (0.05-2.08 mma).
- Controllable with Android/iOS app IoT Light Smart.
- Input Controls: Not insulated Push button x1, Wifi x1.
- Output Sync: DALI x1.
- Printed Circuit UL.
- Protection Class: IP20.
- Standard Dimension 40x80x24.45 mm.
- Dimension with accessories 40x100x24.45 mm.
- Works with Hey Google.
- Compatible with Amazon Alexa Voice Assistant through the skill IoTLight.
- Works with IFTTT.
- All connections must be made with non-live devices and carried out by specialized personnel.
- Use only in dry conditions.
- Google and all related marks are trademarks of Google Inc. or its affiliates.
- Amazon, Alexa, and all related marks are trademarks of Amazon.com, Inc. or its affiliates..
- IFTTT and all related marks are trademarks of IFTTT Inc. or its affiliates.






















CODE	INPUT	CONTROL	CASE	DIMENSION
	VOLTAGE	INPUTS		mm
2AMCV718WDPS	100-240V AC	Not insulated Push button x1	YES	40x80
		Wifi x1		h 24.45