

24,45

2AMDI569VPWS-1

Mono channel costant voltage WIFI/PUSH

Monochannel Dimmers with Output Voltage PWM.

Input Range: 8-53V DC.

Output Voltage PWM 8-53V DC with current from 0A to 12A (576W at 48V

Controllable with Android/iOS app IoT Light Smart.

Input Controls					
Туре	Qty				
Insulated Push button	1				
Wifi	1				

Output Sync					
Туре	Qty				
PWM	1				



- Monochannel Dimmers with Output Voltage PWM.
- Input Range: 8-53V DC.
- The device is not equipped with earth connection

Protection against accidental contact with live parts is garantied by the enclosure.

- Power Connector Cross-section of conductors 14-30 AWG (0.05-2.08 mma).
- Interface Connector Cross-section of conductors 15-30 AWG (0.05-1.65 mma).
- Output Voltage PWM 8-53V DC with current from 0A to 12A (576W at 48V DC).
- Controllable with Android/iOS app IoT Light Smart.
- Input Controls: Insulated Push button x1, Wifi x1.
- Output Sync: PWM x1.
- PWM Frequency: 390 Hz.
- Printed Circuit UL.
- Protection Class: IP20.
- Standard Dimension 40x80x24.45 mm.
- Dimension with accessories 40x100x24.45 mm.
- Works with Hey Google.
- Compatible with Amazon Alexa Voice Assistant through the skill IoTLight.
- Works with IFTTT.
- Open circuit protection.
- To supply the device you have to use a SELV power supply in order to maintain the required elettrical security level.

All connections must be made with non-live devices and carried out by specialized personnel.

- If the control voltage of the PUSH input is higher than the SELV voltage it is necessary to use the OPTIONAL terminal / cable cover to keep the product in CLASS II.
- Use only in dry conditions.
- Google and all related marks are trademarks of Google Inc. or its affiliates.
- Amazon, Alexa, and all related marks are trademarks of Amazon.com, Inc. or its affiliates...
- IFTTT and all related marks are trademarks of IFTTT Inc. or its affiliates.
























CODE	INPUT	(MAX) OUTPUT	N. OUTPUT	MAX OUTPUT	CONTROL	CASE	DIMENSION
	VOLTAGE	CURRENT	CHANNELS	POWER	INPUTS		mm
2AMDI569VPWS-1	8-53V DC	12A	1	576W at 48V DC	Insulated Push button x1	YES	40x80
					Wifi x1		h 24.45